



INTRODUCING THE 940 NUTRI-PLACER 60' & 65' Swath



In MN



800.736.3525

In IA



800.747.8300

WORTH THE WAIT! THE CASE IH 940 NUTRI-PLACER.

See it at the Midwest Ag Industries Exposition (MAGIE) in Bloomington, Illinois August 18-19, 2010 and at the Farm Progress Show in Boone, Iowa Aug. 31 – Sept. 2, 2010. Visit with Case IH experts to learn all about the new 940 Nutri-Placer and learn why it's been well worth the wait!

- 7-section fold, 5 section flex frame for ground contouring
- High under frame clearance for residue flow
- Heavy duty running gear
- 23% increase in width
- Matched capacity to largest tractors in the industry
- Compatible with commodity air systems
- Slim design for narrow transport; excellent roading
- Proven ground-engaging components for NH3 retention
- Hydraulic single point depth control
- Independent pivoting coulters
- High clearance shank with adjustable holding power
- 15- and 30-inch row spacing
- All new rear hitch for simple, reliable hook-up
- Easy leveling turnbuckles for fore/aft pitch and wing wheel adjustment
- Reduced service requirements
- Heavy frame tube

MODEL	940 NUTRI-PLACER	
Model sizes	60 ft. (18.3 m)	65 ft. (19.8 m)
Standard	24 shank HCS on 30 in. (762 mm) centers with 24 in. (610 mm) coulters	26 shank HCS on 30 in. (762 mm) centers with 24 in. (610 mm) coulters
Optional	47 shanks HCS on 15 in. (381 mm) centers with no coulters	51 shanks HCS on 15 in. (381 mm) centers with no coulters
Transport height	13 ft. 9 in. (4.2 m)	13 ft. 9 in. (4.2 m)
Transport width	18 ft. 9 in. (5.7 m)	18 ft. 9 in. (5.7 m)
Main transport wheels	Walking tandem 4x16.5x16.1 14 ply	Walking tandem 4x16.5x16.1 14 ply
Wing wheels	Walking tandem 8x12.5L-15 10 ply	Walking tandem 8x12.5L-15 10 ply
Outer gauge wheel	None	Pin adjust 2x20.5-8 load range D
Weight	22,500 lb (10 206 kg)	23,000 lb (10 433 kg)
Configuration	5 section flex, 7 section fold (fold forward outer wing)	5 section flex, 7 section fold (fold forward outer wing)
HP requirement	360-480	420-560
Knife options	All side mounted	All side mounted
Operating speed	5-8 mph (8-12.9 kph)	5-8 mph (8-12.9 kph)
Depth adjustmt.	Single point hydraulic	Single point hydraulic
Hinge lubrication	Poly bushing non-greasable	Poly bushing non-greasable



⚠ Safety Never Hurts!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.

Case IH is a registered trademark of CNH America LLC.

Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

Availability of some models and equipment builds vary according to the country in which the equipment is used.